



# | Anker SOLIX Solarbank 3 E2700 Pro



PV Terminal		
Max PV Input Voltage		60VDC
Max PV Input Current		4× 32ADC
Max Isc PV		4× 40ADC
Max MPPT Input Power (Total)		3,600W
Operation Voltage Range		16-60VDC
Number of MPPT		4
Battery Data		
Battery Type		Rechargeable LFP Battery
Nominal Voltage		25.6VDC
Max Charging Current		70ADC
Max Discharging Current		75ADC
Rated Power (Single Device)		1,800W
Rated Capacity		2,688Wh
Rated Capacity		105Ah
IEC Code		IFpP52/161/120[8S]M/-20+50/90
AC Input (On-Grid Terminal)		
Max Input Power		2,000W
Max Input Current		10AAC
Max Charging Power		1,200W
Max Charging Current		5.3AAC
Nominal Input Voltage		L+N+PE 220/230VAC, 50Hz
AC Output (On-Grid Terminal)		
Max Output		1,200W
Max Output Current		5.3AAC
Nominal Output Voltage		L+N+PE 220/230VAC, 50Hz
Power Factor Range		0.8 Lagging to 0.8 Leading
AC Output (Off-Grid Terminal)		
Max Output		1,200W
Max Output Current		5.3AAC
Max Bypass Output		2,000W
Max Bypass Output Current		10AAC
AC Nominal Output Voltage		L+N+PE 220/230VAC, 50Hz
General Parameters		
Protective Class		Class I
Ingress Protection		IP65
Inverter Topology		Isolated
Operating Temperature Range		-20°C to 55°C
Max Altitude		4,000 m
Warranty		10 Years
Protection		
Overvoltage Protection		Yes
Undervoltage Protection		Yes
Overcurrent Protection		Yes
Short-Circuit Protection		Yes
Overheating Protection		Yes
Overcharge Protection		Yes
Overdischarge Protection		Yes
Islanding Detection		Yes
Insulation Impedance Detection		Yes
Surge Protection		Yes
Dimensions and Weight		
Dimensions (Solarbank 3 E2700 Pro)		460 × 254 × 279 mm
Net Weight (Solarbank 3 E2700 Pro)		29.2 kg
Dimensions (BP2700 Expansion Battery)		460 × 233 × 217.5 mm
Net Weight (BP2700 Expansion Battery)		24 kg

## | Unboxing

### In the Solarbank 3 Pro Package

	Anker SOLIX Solarbank 3 E2700 Pro		AC Cable with Schuko Plug (3 m)		PV Connector Wrench		Documents
---	-----------------------------------	---	---------------------------------	--	---------------------	---	-----------

### In the Expansion Battery Box (Ordered separately)

	Anker SOLIX BP2700 Expansion Battery		Interlocking Kit Fixed Bracket x2 Screw (M5 10 mm) x2		Wall Mount Kit L-Shape Wall Mount Fitting x2 Expansion Screw (M5 60 mm) x2 Screw (M5 10 mm) x2		Documents
---	--------------------------------------	---	---	--	---	---	-----------

# Anker SOLIX Solarbank 3 E2700 Pro

Revolutionary Power, Breakthrough Savings  
The World's First 3,600W AI-Driven Balcony Solar Power Storage



3,600W  
Solar Input  
4 MPPT

Up to €1,566<sup>1</sup>  
in Annual Savings



1,200W

Bi-Directional  
Charging



Anker  
Intelligence™  
Energy Usage and Savings

0 Waste

InfiniPower™

10  
Years

Warranty

15  
Years

Lifespan

NORD POOL

TOU and Dynamic Tariffs

2.68-16kWh

Expandable  
Capacity



smart meter. The results are derived from the electricity tariffs, and their consumption of

electricity

Phone  
Email:

Note: Pro  
website

official



LinkedIn



Website